PFISTERER

2DIREKT Four Wire Transformer Terminal Clamp

for terminal bolts compliant with DIN EN 50386.

For **horizontal** or **vertical** connection of Cu or Al cables to the secondary side of distribution transformers with DIN EN 50386 compliant bolted connections (1 kV).

2DIREKT terminal clamps are type tested in compliance with IEC 61238 with Cu cables, 240 mm^2.

Width across flats 8 for thrust bolts, 55 Nm.
Width across flats 6 for cheese-head bolts, 25 Nm.

Other types on request.



Picture may vary.

Technical Data

Article no.		331 747 005
Number of conductor		4
Connection possibility		horizontal, vertical
Conductor Cross Sections	(mm^2)	35 - 240
Conductor type		round stranded flexible, round stranded, sector shaped stranded
Bolted connection	(mm)	M12
Transformer size	(kVA)	100/160
Maximum current	(A)	250
Earthing possibility		yes
min. distance between termination	(mm)	97
Material		Body: high-strength Al alloy, tin-plated Screws: steel, hot-dip galvanized

Dimensions

Length	(mm)	84
Width	(mm)	64
Height	(mm)	74

© 2018 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications